Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Le	ed Labs Lighting
-----------------------------------	------------------

Supplier's address: LED Labs Sp. z o.o., ul. Zakopiańska 2C, 30-418 Kraków Polska

Model identifier: WI-3Y12V6NW9520

Type	٥f	liaht	SOLI	rco.
ivbe	UI	ווצוונ	SOU	rce:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	wire		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

Product parameters

D		\(\frac{1}{2} \)	D	\(\sigma_1 \)
Parameter		Value	Parameter	Value
		General product p	arameters:	
	mption in on- 100 h), rounded st integer	3	Energy efficiency class	G
indicating if it r in a sphere (3	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	255 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode pexpressed in W	oower (P _{on}),	3,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00
for CLS, expres	idby power (P _{net}) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	95
Outer	Height	3	Spectral power	See image
dimensions	Width	10	distribution in the	in last page

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	500	range 250 nm to 800 nm, at full-load	
Claim of equival	ent power ^(a)	-	If yes, equivalent power (W)	-
			Chromaticity	0,380
			coordinates (x and y)	0,383
Parameters for LED and OLED light sources:				
R9 colour rende	ring index value	95	Survival factor	1,00
the lumen main	tenance factor	0,96		

(a)'-': not applicable;

(b)_{'-'} : not applicable;

