Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:	: Led Labs Lighting
--------------------------------	---------------------

Supplier's address: LED Labs Sp. z o.o., ul. Zakopiańska 2C, 30-418 Kraków Polska

Model identifier: WI-3YB12V16WW80HS

T	- 6	10 - 1		
Type	Λt	liont	COLIF	CD.
IVDC	vı	HEIL	JUUI	·c.

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	wire		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	Nie
Colour-tuneable light source:	Nie	Envelope:	-
High luminance light source:	Nie		
Anti-glare shield:	Nie	Dimmable:	Only with specific dimmers

Product parameters

Parameter		Value	Parameter	Value
		General product p	arameters:	
	mption in on- 100 h), rounded est integer	8	Energy efficiency class	F
indicating if it r in a sphere (3	us flux (φuse), refers to the flux 60º), in a wide in a narrow cone	785 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode pressed in W	oower (P _{on}),	8,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00
for CLS, expre	ndby power (P _{net}) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer	Height	3	Spectral power	See image
dimensions	Width	10	distribution in the	in last page
Strong 1/2				

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	500	range 250 nm to 800 nm, at full-load	
Claim of equival	ent power ^(a)	-	If yes, equivalent power (W)	-
			Chromaticity	0,421
			coordinates (x and y)	0,389
Parameters for LED and OLED light sources:				
R9 colour rende	ring index value	7	Survival factor	0,90
the lumen main	tenance factor	0,95		

(a)_{'-'}: not applicable;

(b)_{'-'} : not applicable;

