## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Supplier's name or trade mark: | : Led Labs Lighting |
|--------------------------------|---------------------|
|--------------------------------|---------------------|

Supplier's address: LED Labs Sp. z o.o., ul. Zakopiańska 2C, 30-418 Kraków Polska

Model identifier: WI-3YB24V16WW80HS

| _    | •  |       |        |     |
|------|----|-------|--------|-----|
| Tyna | Λt | lioht | source | ٠.  |
| IVDE | vı | HEILL | JUUILE | - • |

| Lighting technology used:     | LED  | Non-directional or directional: | NDLS                       |
|-------------------------------|------|---------------------------------|----------------------------|
| Light source cap-type         | wire |                                 |                            |
| (or other electric interface) |      |                                 |                            |
| Mains or non-mains:           | NMLS | Connected light source (CLS):   | No                         |
| Colour-tuneable light source: | No   | Envelope:                       | -                          |
| High luminance light source:  | No   |                                 |                            |
| Anti-glare shield:            | No   | Dimmable:                       | Only with specific dimmers |

## **Product parameters**

|                                   |  | i Todact para           |  |              |
|-----------------------------------|--|-------------------------|--|--------------|
| Parameter                         |  | Value                   | Parameter  | Value        |
|                                   |  | General product p       | arameters:   |              |
|                                   | mption in on-<br>100 h), rounded<br>est integer                              | 8                       | Energy efficiency class  | F            |
| indicating if it r in a sphere (3 | us flux (фuse),<br>refers to the flux<br>60º), in a wide<br>in a narrow cone | 875 in<br>Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 000        |
| On-mode pressed in W              | oower (P <sub>on</sub> ),  | 8,0                     | Standby power (P <sub>sb</sub> ),<br>expressed in W<br>and rounded to the<br>second decimal  | 0,00         |
| for CLS, expre                    | ndby power (P <sub>net</sub> )<br>ssed in W and<br>second decimal            | -                       | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 80           |
| Outer                             | Height   | 3                       | Spectral power   | See image    |
| dimensions                        | Width  | 10                      | distribution in the  | in last page |
|                                   |  |                         | _  | Dage 1 / 3   |

| without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) | Depth                    | 500  | range 250 nm to 800<br>nm, at full-load |       |
|--|--------------------------|------|---|-------|
| Claim of equival   | ent power <sup>(a)</sup> | -    | If yes, equivalent power (W)            | -     |
|  |                          |      | Chromaticity                            | 0,431 |
|  |                          |      | coordinates (x and y)                   | 0,398 |
| Parameters for LED and OLED light sources:   |                          |      |   |       |
| R9 colour rende  | ring index value         | 2    | Survival factor                         | 0,90  |
| the lumen main   | tenance factor           | 0,95 |   |       |

(a)'-': not applicable;

(b)<sub>'-'</sub> : not applicable;

