Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's	name or	· trade m	ark: Led	Labs Lighting
------------	---------	-----------	----------	---------------

Supplier's address: LED Labs Sp. z o.o., ul. Zakopiańska 2C, 30-418 Kraków Polska

Model identifier: WI-3Y12V12CW80HS

T	- 6	10 - 1- 1		
IVna	α T	IIσnt	source:	,
IVDC	vı	HEILL	Jourte.	

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	wire		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

Product parameters

Froduct parameters					
Parameter		Value	Parameter	Value	
General product parameters:					
<u> </u>	mption in on- 100 h), rounded st integer	6	Energy efficiency class	G	
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		545 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 500	
On-mode power (P _{on}), expressed in W		6,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00	
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80	
Outer	Height	3	Spectral power	See image	
dimensions	Width	10	distribution in the	in last page	
•		-	-	Page 1 / 3	

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	500	range 250 nm to 800 nm, at full-load	
Claim of equival	ent power ^(a)	-	If yes, equivalent power (W)	-
			Chromaticity	0,313
			coordinates (x and y)	0,333
Parameters for LED and OLED light sources:				
R9 colour rendering index value 5		5	Survival factor	1,00
the lumen main	tenance factor	0,96		

(a)'-': not applicable;

(b)_{'-'} : not applicable;

